

PRODUCT INFORMATION SHEET

TETROSYL'S HI-BUILD PRIMER

DESCRIPTION

Tetrosyl Hi-Build Primer offers the ultimate metal protection. Its unique easy to use formula is fast drying, requires minimal sanding and provides a smooth protective base for overcoating that can improve the appearance and extend the lifetime of the final paint finish. For automotive repair work Hi-Build Primer can eliminate the need for stoppers, putty, fillers and undercoats.

ADVANTAGES:

- Use as an anti-rust formula that forms a protective barrier to lock out the effects of weathering and oxidation, giving long lasting protection against rust.
- Fills, levels and primes: Fills minor scratches and surface imperfections. Primes bare metals for bodywork repairs.
- Hi-Build super smooth: Enhanced coverage requires fewer coats with reduced runs and sags.
- Suitable for most automotive rigid plastics, for personalising and colour co-ordination.
- Contains acrylic resins. Combines the strengths of traditional cellulose with the enhanced UV protection and durability of acrylic.
- Fully compatible with all Tetrosyl refinishing products.

Preparation:

- Ensure surface is dry, clean and free from rust. Sand surface and mask off the surrounding area. Fill large holes or dents with bodyfiller. Select correct colour of primer.
- Shake can and test spray on small inconspicuous area.
- Hold can 20-30 cms (8"-12") from surface and spray in alternate horizontal and vertical strokes. Apply several light coats; allow to become tacky in between coats. (about 10 mins).
- Shake can in between coats. Regularly invert & clear sprayhead .In case of blockage, clean sprayhead with cellulose solvent or carefully remove any obstruction with a pin.
- Store and use product at room temperature. Low temperature may cause reduced spray performance.

STORAGE:

Store and use this paint at room temperature. Low temperature below 10 °C may reduce aerosol performance. After use, invert can and spray continuously until nozzle is clear. Ensure can is empty before disposal.

AVAILABILITY

Available in Red Oxide, Grey and White 400ml Aerosols cans

04/12/2008 Page 1 of 2



DISCLAIMER

This Product Information Sheet does not constitute to any extent a fitness for purpose warranty or a quality specification. It is intended to be indicative only of the general characteristics of the product(s) and may not be relied upon (in whole or in part) in substitution of nor as a supplement to any of the information and/or instructions and/or warnings set out on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet (which is available on request).

Neither of the publisher of this Product Information Sheet or the product(s) manufacturer accepts liability for the failure of any person to observe and follow the information and/or instructions and/or warnings on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet.

Any person selecting and using or causing the product(s) to be used for a specific purpose or any third party recommending the product(s) for a specific purpose without in either case first making all appropriate inquiries as to the suitability of the product(s) for the intended purpose does so at his/her/their own risk and no liability is accepted by the publisher or the product(s) manufacturer for any consequent loss, damage or injury, other than such liability as may not (by operation of law) be excluded.

This Product Information Sheet does not apply to the use of the product(s) in any combination or with other products or materials.

Users of a product or products marked "For Professional Use Only are deemed to declare and acknowledge for themselves professional levels of skill, knowledge, competence and experience in the selection and use of such product(s).

Product Information Sheets are updated from time to time and inquiries should be made on a regular basis to ensure that this is the latest version available.

TETROSYL LIMITED BEVIS GREEN WORKS WALMERSLEY BURY BL9 6RE 0161 764 5981 0161 797 5899 info@tetrosyl.com

04/12/2008 Page 2 of 2