

## Dual clutch transmission oil 8100

### Description

Superb high-performance oil based on HC-Synthesis oils. The use of an excellent additive combination with extremely shear-resistant viscosity index improvers, modern wear protection additives as well as stable friction agents achieves an excellent coupling performance. This hi-tech lubricant was developed specifically for the requirements of the increasingly prevalent dual clutch transmissions (DCT). Dual clutch transmission oil 8100 is especially also suited for dual clutch transmissions equipped with a shared oil supply for clutch, synchronisation, gear set and hydraulic control.

### Effect:

- extreme shear stability
- superb wear protection
- great low temperature properties
- good ageing and oxidation stability
- optimal viscosity

### Properties

- optimum stability to aging
- excellent wear resistance
- outstanding resistance to oxidation
- very good low-temperature properties
- excellent shear stability
- excellent viscosity/temperature properties

### LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

BMW 83 22 0 440 214 • BMW 83 22 2 147 477 • BMW 83 22 2 148 578 • BMW 83 22 2 148 579 • BMW DCTF-1 • BMW MTF LT-5 • Chrysler • Ford WSS-M2C 936-A • MB 236.21 • Mitsubishi MZ320065 Dia-Queen SSTF-I • Nissan WSS-M2C 936-A • Peugeot Citroen (PSA) 9734.S2 • Porsche 999.917.080.00 • Volvo 1161839 • Volvo 1161838 • VW G 052 182 • VW G 052 529

### Technical data

Viscosity at 40 °C	33,0 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	6,85 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -40 °C	<20000 mPas DIN 51398
Viscosity index	174 DIN ISO 2909
Color / appearance	gelblich



### Technical data

Density at 15 °C	0,855 g/cm <sup>3</sup> DIN 51757
Flash point	200 °C DIN ISO 2592
Pour point	-48 °C DIN ISO 3016

### Areas of application

Specially developed for use in dual-clutch transmissions (DCT transmissions) in vehicles made by Audi and the VW Group. Usage according to the prescribed specifications from the unit or vehicle manufacturer.

### Application

The specifications and regulations of the unit or vehicle manufacturers must be observed. The optimal effectiveness is achieved only when used unmixed.

### Available pack sizes

1 l Can plastic	20044 GB-F-E-USA-CAN
5 l Canister plastic	20116 GB-F-E-USA-CAN
20 l Canister plastic	20046 GB-F-E-USA-CAN

**Our information is based on thorough research and may be considered reliable, although not legally binding.**