

Leichtlauf Performance SAE 10W-40

DESCRIPTION

Liqui Moly Leichtlauf Performance SAE 10W-40 is a semi-synthetic high-performance, low-friction engine oil with a modern additive technology. It is suitable for year-round use in petrol and passenger vehicle diesel engines with and without exhaust-gas turbocharging and charge air cooler and therefore satisfies the requirements of the latest engine designs.

PROPERTIES

- smooth engine running
- rapid oil delivery at low temperatures
- high lubrication reliability at high and low temperatures
- high shear and ageing stability
- optimum engine cleanliness
- good wear protection
- tested with catalytic converters and performance proved with turbochargers
- saves petrol and reduces pollutant emission
- miscible and compatible with commercially-available engine oils.

Specifications / Approvals:

API SL/CF


ACEA A3-04/B3-04

LIQUI MOLY recommends this product for vehicles for which the following specifications are required:

MB 229.1

TECHNICAL DATA

Viscosity class	:	10W-40	
ASTM colour	:	L5,0	
Density at 15 °C	:	0.870	g/cm ³
Viscosity at 40 °C	:	95,5	mm ² /s
Viscosity at 100 °C	:	14.2	mm ² /s
Viscosity index	:	153	
Flash point	:	230	°C
Pour point	:	-30	°C



PRODUKTI NFORMATION



APPLICATION

Optimum oil for modern petrol and passenger vehicle diesel and turbocharged engines with and without charge air cooling. Suitable where there are long intervals between oil changes and high engine requirements.

INSTRUCTIONS

The operating instructions of the vehicle and engine manufacturers must be followed.

AVAILABLE PACK SIZE

Leichtlauf Performance SAE 10W-40

1 l	Part no. 2535 D-GB-I-E-P
4 l	Part no. 8998 D-NL-F-GR-ARAB
5 l	Part no. 2536 D-GB-I-E-P
20 l	Part no. 2537 D
60 l	Part no. 2101 D
205 l	Part no. 2102 D

PI 04/12/12

Our information is based on thorough research and may be considered reliable, although not legally binding.

