

Top Tec 6610 0W-20

Description

Premium low-friction motor oil based on synthetic technology. Ensures optimum lubrication, outstanding lubricating film stability and minimum wear and deposits even under extreme loads. Ideally suited for engines with start/stop system. Guarantees maximum performance with low fuel consumption.

Properties

- smooth engine running
- outstanding engine cleanliness
- excellent wear protection
- high shear stability
- saves fuel and reduces pollutant emissions
- high lubrication reliability
- optimum stability to aging
- excellent high and low temperature behavior
- long engine service life
- optimum oil pressure under all operating conditions
- tested for turbochargers and catalytic converters

Approvals

ACEA C5 • API SP • Ford WSS-M2C 952-A1 • Jaguar / Land Rover STJLR.03.5006 • MB-Approval 229.71 • Opel OV0401547

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

GM dexos D

Technical data

SAE class (engine oils)	0W-20 SAE J300
Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	39 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	8 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -35 °C (CCS)	≤ 6200 mPas ASTM D 5293
Viscosity index	185 DIN ISO 2909
HTHS at 150°C	≥ 2,6 mPas ASTM D 5481
Pour point	-42 °C DIN ISO 3016



Technical data

Evaporation loss (Noack)	11 % CEC-L-10-A-93
Flash point	220 °C DIN ISO 2592
Total base number	9,5 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 % DIN 51575
Color number (ASTM)	L 3,0 DIN ISO 2049

Areas of application

For gasoline and diesel vehicles. Specially developed for the requirements of Ford, Jaguar / Land Rover, Mercedes-Benz, Opel, GM and other manufacturers.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed! Optimum effectiveness is only possible when the product is used unmixed.

Available pack sizes

1 l Canister plastic	21660 D-BOOKLET
4 l Canister plastic	21661 BOOKLET
5 l Canister plastic	21662 D-BOOKLET
20 l Canister plastic	21663 D-BOOKLET
60 l Drum sheet metal	21664 D-GB
205 l Drum sheet metal	21666 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.