# **Product information**

# LM 48 Installation Paste



# **Description**

MoS2 assembly paste with a selection of solid lubricants. Due to a special preparation process, suitable for the highest requirements.

## **Properties**

- outstandingly adherent
- high capacity
- high wear resistance
- good corrosion protection
- low coefficient of friction
- easy to use
- outstanding emergency-running properties
- highly economical

#### **Technical data**

Color / appearance schwarz / black

Base Mineralöl / mineral oil
Additives MoS2 33, Graphit 6 /

MoS2 33, Graphite 6 %

Density at 20 °C 1 g/ml Pressfit test (no stick slip)  $0,12 \mu$  Thread friction  $0,09 \mu$ 

Operating temperature - 35 bis + 450 / - 35 to +

range 450 °C

Form pastös, flüssig / pastelike,

liquid

Odor geruchslos / odourless

Viscosity at 40 °C <7 mm²/s Flash point 101 °C

# Areas of application

Assembly, repair and maintenance in all areas of engineering. For basic lubrication and preventing running-in damage. Running in sliding surfaces and slip bearings. "For-life" lubrication of joints and small components and for reducing wear on sliding machine components.

# **Application**

Apply to cleaned surfaces using a paint brush, brush or lint-free cloth. Do not rub in. Can be applied in excess.

# Available pack sizes

50 g Tube plastic 3010

D



1 kg Can sheet metal 4096

D-GB-I-NL-F

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-13 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de Service-hotline: 0800/8323230 Technical hotline: +49 (0)731/1420-871 www.liqui-moly.de