Product information

Copper Paste



Description

Release agent and lubricant made from ultra-fine copper particles for use with machine elements subject to high thermal stress. Makes dismantling easy after long running times. Copper paste is used at extreme temperatures for bolted connections and interfaces exposed to high temperatures, pressures, and corrosive elements.

Properties

- resistant to acceleration forces
- prevents transmission of vibration
- long-term corrosion protection
- high bond strength
- outstanding thermal stability
- protects from welding and seizing
- distinctive high-pressure characteristics
- resistant to hot water, salt water and splash water
- universal application
- eliminates squeaks
- lubricant and release effect

Technical data

NLGI number 1/2

DIN 51818

Worked penetration 300 1/10 mm

DIN ISO 2137

Dropping point kein

DIN ISO 2176

Oil separation after 7 days 3,1 %

at 40 °C

of water

DIN 51817

Oil separation after 18 1,1 % hours at 40 °C DIN 5

DIN 51817

Flow pressure at -30 °C <1400 mbar

DIN 51805

Behavior in the presence 1-90

DIN 51807 Teil 1

Viscosity at 40 °C 110 mm²/s

only at 40 C

ASTM D 7042-04

Flash point 220 °C

DIN ISO 2592

Pour point -24 °C

DIN ISO 3016

Areas of application

Used for lubrication, separation, and as a corrosion inhibitor for components exposed to high thermal load. Chemical and petrochemical industry, power stations, ceramic industry, engineering and motor vehicle construction - particularly for bolted connections on exhaust manifolds, silencers, chassis com-

ponents, and brake systems.

* Please follow the manufacturer's advice with regard to products which contain copper.

Application

Apply to cleaned surfaces using a paint brush, brush or lint-free cloth. Apply the amount which is appropriate for the application.

Available pack sizes

100 g Tube plastic 3080

D-GB-E

100 g Tube plastic 2869

GB-DK-FIN-N-S

250 g Brush-in-cap can 3081

sheet metal D-GB-I-E-P

500 g Can plastic 1829

D-NL-F-GR-ARAB

1 kg Can sheet metal 4061

D-GB-I-E-P

1 kg Can sheet metal 1848

D-NL-F-GR-ARAB

Our information is based on thorough research and may be considered reliable, although not legally binding.