

Top Tec ATF 1900

Description

Top Tec ATF 1900 is one of the new generation of high-performance oil for automatic transmissions. It is based on selected basic oils and modern, high-performance additives. The low viscosity helps to reduce the fuel consumption and increases the efficiency. The excellent stability of the friction coefficient enables extended oil change intervals.

Properties

- reduces fuel consumption
- excellent viscosity/temperature properties
- outstanding friction characteristics
- high efficiency
- very good low-temperature properties

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

MB 236.15

Technical data

Density at 15 °C	0,840 g/cm ³ DIN 51757
Viscosity at 40 °C	15,4 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	4,5 mm ² /s ASTM D 7042-04
Viscosity at -40°C (Brookfield)	<= 20000 mPas ASTM D 2983-09
Viscosity index	233 DIN ISO 2909
Pour point	-60 °C DIN ISO 3016
Flash point	180 °C DIN ISO 2592
Color / appearance	blau

Areas of application

Developed for the new generation of Mercedes-Benz 7-gear automatic transmission type 722.9, manufacturing date from 21/06/2010 (except vehicles with engine 629).

Application

The specifications and regulations of the unit or vehicle manufacturers must be observed. Do not mix with oils which have other specifications!



Available pack sizes

1 l Can plastic	3648 D-GB-I-E-P
1 l Can plastic	20028 GB-F-E-USA-CAN
20 l Canister plastic	3649 D-GB-I-E-P
20 l Canister plastic	20030 GB-F-E-USA-CAN
60 l Drum sheet metal	20615 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.