

Top Tec ATF 1800

Description

Low-viscosity high-performance oil of the new generation for automatic transmissions. It is based on synthesis technology with modern, high-performance additives. Aside from excellent ageing and oxidation stability, optimal shifting is guaranteed under all operating conditions thanks to the extremely high viscosity index. It enables long oil change intervals.

Properties

- excellent viscosity/temperature properties
- prevents foam formation
- enables a multifaceted range of applications
- stable to oxidation
- outstanding friction characteristics
- high resistance to aging
- very good low-temperature properties
- excellent corrosion protection
- high wear resistance
- outstanding resistance to oxidation

Specifications and approvals:

Dexron VI • Mercon LV

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Aisin Warner AW-1 • BMW 83 22 2 305 396 • BMW 83 22 2 305 397 • BMW 83 22 2 152 426 • BMW 83 22 0 142 516 • BMW 83 22 2 289 720 • BMW M-1375.4 • Fiat 9.55550-AV5 • JWS 3324 (Aisin Warner) • Land Rover TYK 500050 • Honda ATF DW-1 • Hyundai SP IV • Mazda ATF FZ • Nissan AT-Matic S Fluid • Toyota WS • VW G 055 005 • VW G 055 540 • VW G 060 162

Technical data

Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	25,7 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	5,5 mm ² /s ASTM D 7042-04
Viscosity at -40°C (Brookfield)	<= 10000 mPas ASTM D 2983-09
Viscosity index	159 DIN ISO 2909
Pour point	-48 °C DIN ISO 3016
Flash point	210 °C DIN ISO 2592



Technical data

Color / appearance bräunlich/brownish

Areas of application

Developed for ZF 6HP19/26/32 and ZF 8HP 45/55/70/90 type automatic transmissions that are installed in various Audi, BMW, Jaguar, Land Rover, Porsche, etc. vehicles. Meets further specifications, allowing it to cover an even wider range of vehicles. Usage according to the prescribed specifications from the unit or vehicle manufacturer.

Application

The specifications and regulations of the unit or vehicle manufacturers must be observed. The optimal effectiveness is achieved only when used unmixed.

Available pack sizes

1 l Can plastic	3687 D-GB-I-E-P
1 l Can plastic	9704 D-GB-F-ARAB
1 l Can plastic	20032 GB-F-E-USA-CAN
1 l Can plastic	2381 D-RUS-UA
5 l Canister plastic	20662 D-GB-I-E-P
20 l Canister plastic	3688 D-GB-I-E-P
20 l Canister plastic	20034 GB-F-E-USA-CAN
60 l Drum sheet metal	3689 D-GB
205 l Drum sheet metal	20624 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.