

## Top Tec ATF 1400

### Description

Top Tec ATF 1400 is a high performance automatic transmission fluid of the new generation based on synthetic technology. It was developed specifically for use in CVTs with thrust link belt or a gear chain made of steel. The basis of modern base oils and select additives offer the best possible anti-froth protection, which is necessary for CVTs. It also features a very good stability against aging and oxidation. Top Tec ATF 1400 is tried and tested, most notably in the Mercedes-Benz A-Class and B-Class Autotronic transmissions and in continuously variable automatic transmissions (Multitronic) in Audi vehicles.

### Properties

- outstanding friction characteristics
- very good low-temperature properties
- excellent wear resistance
- prevents foam formation
- outstanding resistance to oxidation
- excellent corrosion protection
- excellent viscosity/temperature properties
- extremely stable to aging

### LIQUI MOLY recommends this product for vehicles for which the following specifications are required:

Dodge NS-2 • Dodge CVTF+4 • Ford CVT23 • Ford CVT30/MERCON C • GM/Saturn DEX-CVT • Honda HMMF • Hyundai SP III • Jeep CVTF+4 • Jeep NS-2 • Kia SP III • Mini Cooper (EZL 7/99) • Mitsubishi CVTF-J1 • Mitsubishi SP-III • MB 236.20 • Nissan CVT NS-2 Fluid • Subaru Lineartronic CVTF • Subaru NS-2 • Suzuki NS-2 • Suzuki TC • Suzuki CVT Green1 • Toyota TC • VW G 052 180 • VW G 052 516

### Technical data

Density at 15 °C	0,850 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	32,6 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	7,0 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -40°C (Brook-field)	<= 20000 mPas ASTM D 2983-09
Viscosity index	184 DIN ISO 2909
Flash point	200 °C DIN ISO 2592
Pour point	-45 °C DIN ISO 3016



### Technical data

Color number (ASTM)	L2,5
	DIN ISO 2049

### Areas of application

For the new generation of CVTs with thrust link belt or a gear chain made of steel.

### Application

The specifications and instructions from the unit or vehicle manufacturer must be followed. Optimum effectiveness is only possible when the product is used unmixed.

### Available pack sizes

1 l Can plastic	3662 D-GB-I-E-P
1 l Can plastic	3669 D-NL-F-GR-ARAB
1 l Can plastic	20036 GB-F-E-USA-CAN
1 l Can plastic	8041 D-RUS-UA
20 l Canister plastic	3692 D-GB-I-E-P
205 l Drum sheet metal	3661 D

**Our information is based on thorough research and may be considered reliable, although not legally binding.**