

Top Tec 4500 SAE 5W-30

DESCRIPTION

Top Tec 4500 is a state-of-the-art, low-ash low-friction motor oil of top quality for use all year round. The combination of unconventional base oils using synthetic technology together with the latest additives guarantees a motor oil that provides exceptional protection against wear and reduces fuel consumption while ensuring fast oil penetration of the engine. The vehicle manufacturers such as Jaguar, Land Rover, Mazda and Mitsubishi require a motor oil with this specification for various vehicle models. Ensures maximum service life of the diesel particulate filter (DPF). In addition, Top Tec 4500 5W-30 is best suitable for gas fuelled (CNG/LPG) passenger cars.

PROPERTIES

- Smooth engine running
- Long engine service life due to exceptional protection against wear
- Rapid oil delivery at low temperatures
- Optimum oil pressure at all engine speeds
- High shear and aging stability
- With maximum fuel savings thanks to decreased HTHS viscosity
- Outstanding engine cleanliness
- Tested with catalytic converters and performance proven with turbochargers
- Ensures maximum service life of the diesel particulate filter
- Optimum effectiveness only when the product is used unmixed.

Specifications and approvals:

ACEA C1-08

JASO DL-1

Ford WSS-M2C 934-B


LIQUI MOLY also recommends this product for vehicles for which the following specifications are required:

Mazda

Mitsubishi

TECHNICAL DATA

Viscosity class	: 5W-30	
Density at +15 °C	: 0.850 g/cm ³	DIN 51757
Viscosity at +40 °C	: 53.5 mm ² /s	DIN 51562
Viscosity at +100 °C	: 10 mm ² /s	DIN 51562
Viscosity index	: 177	DIN ISO 2909
Flash point	: 228 °C	DIN ISO 2592
Pour point	: - 36 °C	DIN ISO 3016
ASTM color number	: 3	DIN 51578
HTHS viscosity	: >2,9 mPas	ASTM D 4683
Total Base Number	: 6,0 mg KOH/g	DIN ISO 3771



PRODUKTTINFORMATION



AREAS OF APPLICATION

For various vehicles from the newest generation from the companies Jaguar, Mazda and Mitsubishi. Suitable for turbochargers and catalytic converters.

APPLICATION


The operating instructions of the vehicle and engine manufacturers must be followed.
Full effectiveness can only be ensured when the product is not mixed!

AVAILABLE PACK SIZES

Top Tec 4500 SAE 5W-30	1 l	Part no. 3724 D-GB-I-E-P
	1 l	Part no. 2317 D-NL-F-GR-ARAB
	5 l	Part no. 3729 D-GB-I-E-P
	5 l	Part no. 2318 D-NL-F-GR-ARAB
	20 l	Part no. 3731 D
	60 l	Part no. 3732 D
	205 l	Part no. 3733 D
	bulk oil	Part no. 3734

PI 07/09/11

Our information is based on thorough research and may be considered reliable, although not legally binding.



LIQUI MOLY GMBH
Jerg-Wieland-Str. 4
D-89081 Ulm-Lehr

Postfach 28 29
D-89018 Ulm
www.liqui-moly.de

Phone: +49-(0)731/1420-13
Fax: +49-(0)731/1420-82
e-mail: info@liqui-moly.de

Service Hotline: 0800/8323230
Technische Hotline: +49-(0)731/1420-13