

Weld Protection Spray

DESCRIPTION

Weld Protection Spray is a combination of agents for preventing splutter at the welding nozzle or tip and the surface of the material without impairing the weld. Weld Protection Spray has been formulated according to the latest technology.

PROPERTIES

- prevents adhesion of welding beads on the workpiece and the torch
- increases the service life of the welding nozzle and the inner components of the torch
- used for steel, aluminium and stainless steel
- does not contain silicones
- does not contain chlorofluorohydrocarbons

TECHNICAL DATA

| | |
|---------------------|--------------------------|
| Colour | : white |
| Substance | : liquid |
| Basis | : talc |
| Density up to 20 °C | : 0.67 g/cm ³ |
| Propellant | : propane/butane |
| Solubility in water | : insoluble |

APPLICATION

Used for all welding work on steel, aluminium and stainless steel.

INSTRUCTIONS

Briefly shake the aerosol can. Switch off the welding equipment and spray a thin coat on the cold workpiece and the torch.

Directions: Do not spray onto workpieces or parts of the torch while still glowing! Adhere to drying time of at least 5 minutes!

AVAILABLE PACK SIZE

| | | |
|-----------------------|----------------|--------------------------|
| Weld Protection Spray | 500 ml aerosol | Part no. 4086 D-GB-I-E-P |
|-----------------------|----------------|--------------------------|

PI 04/10/09

Our information is based on thorough research and may be considered reliable, although not legally binding.

