

Air Conditioning System Cleaner

DESCRIPTION

Cleaning fluid for removing mold and bacteria (e.g. legionellae) from A/C systems in passenger cars, commercial vehicles, buses and in the home without the need for dismantling. After cleaning, this product leaves behind a pleasant fresh fragrance.

PROPERTIES

- removes musty smells
- exterminates bacteria and moulds
- forms a protective film on the evaporator
- provides fresh clean air
- increases comfort when travelling
- expert's microbiological report available

TECHNICAL DATA

Basis	: disinfectant/odour remover
Colour	: colourless
Form	: liquid
Density at 20 °C	: 1.0 g/cm ³
Flash point	: < 0 °C
Solubility in water	: miscible
Shelf-life	: 2 years unopened can

APPLICATION

Used for cleaning and disinfecting air conditioning systems in passenger motor vehicles and commercial vehicles. The product can also be used for domestic air conditioning systems.


INSTRUCTIONS

Portion pack: One can will treat one vehicle or one A/C system. If the manufacturer of the A/C system offers a cleaning service recommendation, this recommendation must be observed. If no model-specific instructions are available from the passenger car manufacturer, follow the LIQUI MOLY recommendation for application. Spray the cleaning fluid directly on the surface of the evaporator (if possible) for commercial vehicle, bus and home A/C systems.

LIQUI MOLY Recommendations for use

- During the cleaning process, make sure the window is open and avoid breathing in the vapour when cleaning
- Check to make sure the condensation water drainage opening is not blocked
- If present, remove the dust or pollen filter from the fresh-air intakes

With the following adjustments to the heater and blower, dry the evaporator surface for 10 minutes with the motor running:



PRODUKTTINFORMATION



- switch off the air conditioning unit and set to air circulation
 - set the air distribution switch to footwell
 - turn the temperature regulator and blower selector switch to max.
- Important:** Do not insert the probe too far into the fresh air intake, as the blower motor can be damaged.
- When the container is empty, switch off the blower.
 - Allow Air Conditioning System Cleaner to act for 15 to 30 minutes.
 - Dry the surface of the evaporator for a period of 10 minutes using the same settings for the heater and blower system as those used before cleaning.
 - If necessary, replace the dust or pollen filter.


Note: Wipe up any spilled cleaner using a clean cloth and water.

AVAILABLE PACK SIZE

Air Conditioning System Cleaner	250 ml	Part no. 4087 D-GB-I-E-P
	250 ml	Part no. 7577 D-RUS-UA

PI 05/05/10

Our information is based on thorough research and may be considered reliable, although not legally binding.



LIQUI MOLY GMBH
Jerg-Wieland-Str. 4
D-89081 Ulm-Lehr

Postfach 28 29
D-89018 Ulm
www.liqui-moly.de

Phone: +49-(0)731/1420-13
Fax: +49-(0)731/1420-82
e-mail: info@liqui-moly.de

Service Hotline: 0800/8323230
Technische Hotline: +49-(0)731/1420-13