# **Product information**

PI 15/16/05/2017

# High Performance Gear Oil (GL4+) SAE 75W-90



#### **Description**

Our fully synthetic high-performance gear oil SAE 75W-90 is a top grade, high-pressure gear oil for high-load manual, auxiliary, transaxle and hypoid transmissions, where a lubricant complying with API GL4+ is required. High-quality, synthetic-based oil and modern additive technology ensures a broad application range and optimum transmission lubrication under extreme conditions. The low-viscosity characteristics of this gear oil make it also suitable where shifting difficulties exist (e.g. stiffness or noise generation).

## Sulfate ash

**Technical data** 

0,14 q/100q DIN 51575

Color number (ASTM) L 1.0

**DIN ISO 2049** 

#### **Properties**

- excellent viscosity/temperature properties
- outstanding seal compatibility
- excellent resistance to aging
- excellent wear resistance
- high pressure-absorption capability
- wide viscosity range
- reduces gearshift resistance
- excellent corrosion protection
- reduces transmission noise

# Areas of application

For extreme high-load manual, auxiliary, transaxle and hypoid transmissions, where a lubricant complying with API GL 4+ is required.

### Specifications and approvals:

API GL4+ • Ford ESD-M2C 175-A

#### **Application**

The requirements of the vehicle and transmission manufacturers must be adhered to. Can be mixed with mineral oil residue, which remains in transmission/final drive when changing oil.

### LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

VW 501 50 (G50) • ZF TE-ML 08

#### Available pack sizes

500 ml Can plastic 4433 D-GB-I-E-P

4434 1 l Can plastic

D-GB-I-E-P

1 l Can plastic 8180

D-F-I

1 l Can plastic

D-NL-F-GB-ARAB

1 l Can plastic

GB-F-E-USA-CAN

20 l Canister plastic

D-GB-I-E-P

20014 20 l Canister plastic

GB-F-E-USA-CAN

60 l Drum sheet metal 4436

D-GB

#### **Technical data**

SAE class (gear oils) 75W-90 SAE J306

Density at 15 °C 0,855 g/cm<sup>3</sup>

DIN 51757

Viscosity at 40 °C 81.5 mm<sup>2</sup>/s

ASTM D 7042-04

Viscosity at 100 °C 14,3 mm<sup>2</sup>/s

ASTM D 7042-04

Viscosity at -40°C (Brook-

field)

<= 150000 mPas ASTM D 2983-09

183 Viscosity index

**DIN ISO 2909** 

Pour point -60 °C

**DIN ISO 3016** 

200 °C Flash point

**DIN ISO 2592** 

Our information is based on thorough research and may be considered reliable, although not legally binding.