

## Hypoid Gear Oil TDL SAE 75W-90

### DESCRIPTION

Multi-purpose gear oil for universal application in commercial vehicles. This "TOTAL DRIVE LINE" (TDL) gear oil is most suitable for lubricating all drive elements, from synchronized and non-synchronized manual transmissions to geared axle drives. Because of the reduction in the number of product types and the reduced risk of confusion between them, Hypoid Gear Oil TDL contributes significantly to streamlining the modern vehicle fleet. Reduced friction as a result of the optimum viscosity level helps to save fuel.

#### Specifications / Approvals:

API GL 4, GL 5

API MT1

MIL-L-2105 D

MIL-PRF-2105 E

**LIQUI MOLY recommends this product for vehicles for which the following specifications are required**

ZF TE-ML 12E, 16B, 17B, 19B

VOLVO 97310 (Axle)

DAF

SCANIA STO 1:0

MAN M3343 Typ M (old)


MAN 341 Typ Z2

MAN 342 Typ M2

EATON

### TECHNICAL DATA

Viscosity class	: 75W-90		DIN 51512
Density at +15 °C	: 0.870	g/cm <sup>3</sup>	DIN 51757
Viscosity at +40 °C	: 82.5	mm <sup>2</sup> /s	DIN 51562
Viscosity at +100 °C	: 14.2	mm <sup>2</sup> /s	DIN 51562
Viscosity index	: 179		DIN ISO 2909
Flash point	: 180	°C	DIN ISO 2592
Pour point	: -42	°C	DIN ISO 3016
ASTM color number	: L3,0		DIN ISO 2049



# PRODUKTINFORMATION



## APPLICATION

The operating instructions of the vehicle and transmission manufacturers must be followed.

## AVAILABLE PACK SIZES

Hypoid Gear Oil TDL  
SAE 75W-90

500 ml	Part no. 1406 D-GB-I-E-P
1 l	Part no. 1407 D-GB-I-E-P
1 l	Part no. 2655 D-PL-H-RO-TR
1 l	Part no. 3945 D-RUS-UA
4 l	Part no. 3939 D-RUS-UA
20 l	Part no. 1408 D
60 l	Part no. 4708 D
205 l	Part no. 4709 D
bulk oil	Part no. 4731 D

PI 36/04/13

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

