

## Pro-Line Oil Loss Stop



### Description

Pro-Line Oil Leak Stop rejuvenates rubber and plastic seals in the engine and reduces oil consumption via piston rings and valve guides. Pro-Line Oil Leak Stop counteracts the loss in viscosity of motor oils and puts an end to environmentally pollutant oil patches on the road and in the garage. Compatible with all commercially available motor oils.

### Properties

- prevents blue, smoky exhaust fumes
- suitable for gasoline and diesel engines
- maintains and regenerates rubber and plastic seals
- outstanding elastomer compatibility
- guarantees low oil consumption
- prevents oil spots and pollution of the environment
- reduces engine noise
- remedies leaks at shrunken or porous seals

### Available pack sizes

1 l Can sheet metal                      5182  
D-GB-I-E-P

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

### Technical data

Color / appearance	gelb, klar / yellow, clear
Appearance / properties	viskose Flüssigkeit / viscous liquid
Density at 20 °C	0,896 g/cm <sup>3</sup> DIN 51757
Viscosity at 20 °C	1299 mPas DIN 51398
Flash point	76 °C DIN ISO 2592
Pour point	-5 °C DIN ISO 3016
Form	pastös, flüssig / pastelike, liquid
Odor	charakteristisch / characteristic

### Areas of application

Suitable for all gasoline and diesel engines.

### Application

Contents of the can (1 liter) are sufficient for up to 15 liters of motor oil. The product can be added at any time. After adding, run the engine until warm or drive the vehicle. Sealing first takes place after about 600 to 800 km of driving. To guarantee a lasting effect, we recommend adding Pro-Line Oil Leak Stop after each oil change.

**Note: Not suitable for use in motorcycles with wet clutches!**