

Product information

Tractor Oil UTTO 10W-30

PI 7/17/11/2015



Description

Tractor Oil Utto is a highly developed multi-purpose oil (Utto = Universal Tractor Transmission Oil) which has been specially formulated for forestry and agricultural machinery. This product meets the requirements of today's combined drive systems (transmission and hydraulic) and wet brakes. It therefore represents a special transmission/hydraulic oil with wear protection properties and is stable to oxidation.

Properties

- excellent wear resistance
- stable to oxidation
- excellent resistance to aging
- rationalizes storage
- high pressure-absorption capability
- universal application

Specifications and approvals:

Allison C4 • API GL 4 • Caterpillar TO-2

LIQUI MOLY recommends this product for vehicles for which the following specifications are required:

AGCO Q-1826 • Case (IHC) MS 1204 • Case (IHC) B6 • Case (IHC) MS 1205 • Case (IHC) MS 1206 • Case (IHC) MS 1207 • Case (IHC) MS 1209 • CASE New Holland MAT 3510 • CASE New Holland MAT 3525 • CASE New Holland MAT 3526 • Deutz • Fendt • Ford New Holland M2C41-B • Ford New Holland M2C48-B • Ford New Holland M2C53-A • Ford New Holland M2C86-B • Ford New Holland M2C86-C • Ford New Holland M2C134-A • Ford New Holland M2C134-B • Ford New Holland M2C134-C • Ford New Holland M2C134-D • John Deere J20D • John Deere JDM 3000 TH • Landini • Massey-Ferguson M1135 • Massey-Ferguson M1141 • Massey-Ferguson M1143 • Massey-Ferguson M1145 • New Holland NH 410B • Renault • SAME-Lamborghini • Schlüter • Volvo BM WB 101

Technical data

Viscosity at 40 °C	60 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	9,8 mm ² /s ASTM D 7042-04
Viscosity at -25 °C	<7000 mPas DIN 51377
Viscosity at -26 °C	<150000 mPas DIN 51398
Viscosity index	148 DIN ISO 2909



Technical data

Color number (ASTM)	L1,5 DIN ISO 2049
Density at 15 °C	0,885 g/cm ³ DIN 51757
Flash point	228 °C DIN ISO 2592
Pour point	-36 °C DIN ISO 3016
Foaming behavior at 24 °C	0/0 ml ISO 6247
Foaming behavior at 93.5 °C	40/0 ml ISO 6247
Foaming behavior at 24 °C after 93.5 °C	0/0 ml ISO 6247
Total base number	9,6 mg KOH/g DIN ISO 3771
Sulfate ash	1,5 g/100g DIN 51575
SAE class (gear oils)	10W-30 SAE J306

Areas of application

The optimum product for universal use as a transmission and hydraulic oil including wet brakes in forestry and agricultural machines and equipment.

Application

The operating instructions of the tractor manufacturer must be followed. Can be mixed with all commercially available engine oils. Fully effective only when used alone.

Available pack sizes

20 l Canister plastic	4749 D-GB-I-E-P
60 l Drum sheet metal	4751
205 l Drum sheet metal	6959

Product information

PI 7/17/11/2015



Tractor Oil UTTO 10W-30

Our information is based on thorough research and may be considered reliable, although not legally binding.