



Fuel-efficient Special AA SAE 5W-20


DESCRIPTION Modern premium-class fuel-efficient engine oil, which especially has been developed for the year-round use in Asian and American vehicles. The combination of unconventional base oils on synthesis technology in connection with the latest additives guarantees an engine oil which protects against wear, reduces the oil and fuel consumption, keeps the engine clean and provides for a quick oiling of the engine. According to the instructions of the manufacturer, oil change intervals of up to 40,000 km are realizable.

PROPERTIES - easy engine operation

- long service life of the engine by means of excellent wear protection
- quick oil supply at low temperatures
- ideal oil pressure in all speed ranges
- maximum lubrication reliability at high and low temperatures
- high shear and ageing stability
- reduces the fuel consumption as well as the pollutant emission
- excellent engine cleanness
- exhaust gas catalytic converter tested and turbo proven
- miscible and compatible with standard engine oils

Specifications:

API SM **ILSAC GF-4** LIQUI MOLY recommends this product in compliance with the manufacturer requirements for the following vehicles: Ford WSS-M2C 930-A Ford WSS-M2C 925-A Chrysler MS-6395 Daihatsu Honda Hyundai Kia Isuzu Mazda Mitsubishi DiaQueen Nissan Suzuki Toyota Subaru GM



PRODUKTINFORMATION



TECHNICAL				
DATA	Viscosity class	: 5W-20		
	Density at +15 °C	: 0,850	g/cm³	DIN 51757
	Viscosity at +40°C	: 47	mm²/s	DIN 51562
	Viscosity at +100°C	: 8.7	mm²/s	DIN 51562
	Viscosity index	: 166		DIN ISO 2909
	Flash point	: 214	°C	DIN ISO 2592
	Pour point	: -39	°C	DIN ISO 3016
	Base number	: 7.5	mg KOH/g	DIN ISO 3771
APPLICATION AREAS	Ideal for modern Japanese a case of long oil change interv			
USE	The operational instructions of the car manufacturer and the engine manufacturer are to be observed. The full effectiveness of the product can only be guaranteed if it remains in unmixed condition!			
AVAILABLE PACKAGE SIZE	Fuel-efficient Special AA			
	SAE 5W-20	11	ltem-no. 7620) D-RUS-UA
	0, 12 011 20	41	Item-no. 7621	
		11	Item-no. 7657	D-GB-ARAB-RUS-KZ
		4		B D-GB-ARAB-RUS-KZ
		5 I	Item-no. 7532	2 D-GB-ARAB-RUS-KZ

205 I

Item-no. 7622 D

PI 06/05/12

Our information is based on careful examinations and can be considered reliable. However, it is intended only for giving advice without obligation.



Postfach 28 29 D-89018 Ulm www.liqui-moly.de Phone: +49-(0)731/1420-13 Fax +49-(0)731/1420-82 e-mail: info@liqui-moly.de