

White Universal Grease

Description

For use on high-load plain, roller and rocker bearings. Solid lubricants guarantee high-pressure properties for clean lubrication points and long-life lubrication. Hygienically safe within the meaning of section 31 (1) of the German Foodstuffs and Consumer Goods Act.

Properties

- has a lasting effect
- outstanding slip properties
- increases the lubricating effect

Technical data

Brief description	KF2K-30 DIN 51502
Thickener	Lithiumhydroxystearat
Base	mineral oil
Operating temperature range	-30 to +120 °C
Color / appearance	white
NLGI number	2 DIN 51818
Dropping point	> 195 °C DIN ISO 2176
Viscosity at 40 °C	110 mm ² /s DIN 51562-1
Four-ball tester material load/weld force	3600 N DIN 51350-4
Worked penetration	265-295 DIN ISO 2137

Areas of application

Suitable for lubricating high-load plain, roller and rocker bearings, spindles and guides on machines in the food, beverage, paper, textile and clothing industries as well as on domestic appliances.

Application

Do not mix with other greases!

Available pack sizes

400 g Cartridge plastic	8918 D-NL-F-GR-ARAB
25 kg Bucket plastic	21408 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

