

Product information

Pro-Line PTFE Powder Spray

PI 7/21/04/2015



Description

Greaseless lubricants and release agents based on PTFE (Teflon or Polytetrafluoroethylene). The dry lubricant does not attract dirt and dust. It eliminates squeaks, creaks and stiffness and provides long-lasting protection against wear.

Properties

- high chemical resistance
- Free of oil, grease and silicones
- easy to use
- extremely low friction
- eliminates squeaks
- suitable for care, protection and insulation
- broad operating temperature range

Technical data

Color / appearance	weiß / white
Base	PTFE
Density	0,58 g/ml
Operating temperature range	- 40 bis + 250 / - 40 to + 250 °C
Propellant	Propan, Butan / propane, butane
Flash point	-60 °C
Form	flüssig / liquid
Odor	charakteristisch/ characteristic

Areas of application

Used for lubrication of moving parts like slide rails, hinges, closing parts, belt mechanics, etc., as a release agent or for noise removal of panelling for nearly all materials. Particularly suitable in applications where oil and silicone containing lubricants disturb the post-processing.

Application

The surface must be free of grease, clean and dry. In thin layer application and allow to dry in between. Due to the folding spray pipe a precise spraying is guaranteed. If the spray tube is folded in, a flat spraying is possible. Also sprays overhead.



Available pack sizes

400 ml Can aerosol	7384 D-GB-I-E-P
400 ml Can aerosol	9906 GB-DK-FIN-N-S

Our information is based on thorough research and may be considered reliable, although not legally binding.