

Product information

Grinding Paste

PI 11/01/24/2025



Description

As effective problem solver, this paste effortlessly repairs heavily weathered paintwork, deep scratches, and orange peel and smooths the paint surface. Treated surfaces can then be painted directly. Silicone-free and suitable for polishing machines.

Properties

- suitable for polishing machines
- easy removal of weathered paint layers
- simple to use
- prepares surfaces for painting
- smooths the paint surface

Technical data

Base	grinding agent, solvents
Form	viscous
Color / appearance	white
Odor	characteristic
Density	1,1 g/cm ³
Flash point	> 90 °C
Shelf life in original sealed container	30 months

Areas of application

For repairing deep scratches, orange peel, and extremely weathered paintwork.

Comment

Use care when working with polishing machines, as Grinding Paste 1500 has a strong abrasive effect.

Application

1. Surfaces must be thoroughly cleaned with Car Wash Shampoo and carefully dried before treatment. 2. Shake well before use. 3. Then pour Grinding Paste 1500 onto a Hand Polishing Sponge Hard (part no. 21782) or Microfiber Cloth (part no. 1651) and apply thinly and uniformly using circular motions. Note: Take care at joins in the bodywork as the product is very abrasive! 4. After application, polish off the polish residues with Paintwork Microfiber Cloth (part no. 21783). Recommendation: Then seal with Hard & Protective Wax to provide longer protection for the paint. Note: Do not use under direct heat or on hot paint surfaces!

Available pack sizes

250 ml Tube plastic	23027 GB-F-D-I-NL-ARAB
250 ml Tube plastic	23067 E-P-H-RO-TR-GR



Available pack sizes

250 ml Tube plastic 23107
RUS-PL-CZ-DK-S-FIN-N

Our information is based on thorough research and may be considered reliable, although not legally binding.