



Philips LED Inspection
lamps
Multi-Directional Lighting
System

1 module



LPL05SPAREX1

See better, work better

All-in-one lighting system for professionals

Robust and hands-free, this multidirectional module will provide you the optimal visibility without shadow.

Optimal visibility, no shadow

- High-power LED light
- 300° rotating head
- Light output for one module : 120 lumens (normal mode)
- Light output for one module : 200 lumens (Boost mode)

Hands-free lighting

- 1 multidirectional module

High resistance

- Resistant to chemical & workshop solvents
- Strong impact resistance -IK07
- Water & dust protected -IP54

High autonomy

- Fast Rechargeable, Energy saving LifeP04 battery technology

PHILIPS

Highlights

Light output for one module



Every module of the MDLS solution will provide you a light output of 200 lumens in boost mode. In boost mode the light will last for 3 hours.

Light output for one module



Every module of the MDLS solution will provide you a light output of 120 lumens in normal mode. In normal mode the light will last for 5 hours.

Water & dust protected -IP54



The LED inspection lamp is water resistant, and conforms to IP54.

Strong impact resistance -IK07



Strong impact resistance -IK07

300° rotating head



The 300° rotating head will enable you to achieve a shadow-free workspace for optimum safety and efficiency.

Fast Rechargeable



Fast Rechargeable, Energy saving LifeP04 battery technology. Since the modules are fast charging, whenever one of the modules is charged and ready for the job, you can take it out directly.

High-power LED light



As the international market leader in car lighting, we have years of experience and know-how in light. The Philips LED inspection lamps are equipped with high power LEDs. Our LEDs combine strong light performance with a natural color rendering for fatigue-free work.

Resistant to chemical



As well as resisting knocks, the case for our inspection lamp are resistant to water, chemical and workshop solvents.

1 multidirectional module



1 multidirectional module

Specifications

Maximum visibility

- Light output: 120 lumens, 200 lumens

Robust

- Impact protection rating (IK): IK07
- Ingress protection rating (IP): IP54

Power

- Battery life time: up to 5 hr

Technical specifications

- Operating line voltage: 100-240V

Outer Carton

- Number of consumer packagings: 2
- Outer carton (L x W x H): 18.6 x 7.8 x 11.3 cm
- Gross weight: 0.7 kg
- EAN: 87 27900 38766 7



Issue date 2014-11-08

Version: 2.1.4

12 NC: 9237 956 90101
EAN: 87 27900 38766 7

© 2014 Koninklijke Philips N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips N.V.
or their respective owners.

www.philips.com