



PRODUCT INFORMATION SHEET

CARLUBE 15W-40 MINERAL OIL

DESCRIPTION

Carlube 15W-40 is a high specification, mineral oil based, engine oil meeting the latest API and ACEA requirements. High quality base oils are blended with advanced additives to give high anti-wear and detergency properties, thus providing longer engine life and maintaining maximum performance in terms of power and efficiency.

ADVANTAGES

- Black sludge control
- Good anti-wear protection
- Shear stable VI improver
- Outstanding engine cleanliness
- Catalyst friendly

APPLICATION

Carlube 15W-40 is suitable for use in most modern petrol engines including naturally aspirated and turbo-charged vehicles with multi-valves, fuel injection and twin-cams. Also suitable for light duty diesel applications.

PERFORMANCE LEVEL

- API SL/CF
- ACEA A3/B3/B4

PROPERTIES

SAE Viscosity Grade		15W-40
Density @ 15°C		0.889
Kinematic Viscosity (mm ² /s)	@ 40°C	99.2
	@ 100°C	13.9
Viscosity Index (VI)		142
Pour Point (°C)		-25
Flash Point (°C)		199
Sulfated Ash (%)		
Total Base Number (mgKOH/g)		

AVAILABILITY

1 Litre – XPP010 5 Litre – XPP050 25 Litre – YFA025 199 Litre – YFA199

ENVIRONMENTAL PROTECTION/SAFETY PRECAUTIONS

Do not pour used oil down sewers or drains. Dispose of used oil at your nearest oil-recycling bank. Dispose of empty packs in a responsible manner. Store container in an upright position and secure when transported. Wear goggles if splashing risk. Avoid exposure to oil mist. When using oil do not eat, drink and smoke. Wash hands after use. Always refer to vehicle or engine manufacturers handbook to verify suitability of this product for the vehicle/engine.

**DISCLAIMER**

This Product Information Sheet does not constitute to any extent a fitness for purpose warranty or a quality specification. It is intended to be indicative only of the general characteristics of the product(s) and may not be relied upon (in whole or in part) in substitution of nor as a supplement to any of the information and/or instructions and/or warnings set out on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet (which is available on request).

Neither of the publisher of this Product Information Sheet or the product(s) manufacturer accepts liability for the failure of any person to observe and follow the information and/or instructions and/or warnings on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet.

Any person selecting and using or causing the product(s) to be used for a specific purpose or any third party recommending the product(s) for a specific purpose without in either case first making all appropriate inquiries as to the suitability of the product(s) for the intended purpose does so at his/her/their own risk and no liability is accepted by the publisher or the product(s) manufacturer for any consequent loss, damage or injury, other than such liability as may not (by operation of law) be excluded.

This Product Information Sheet does not apply to the use of the product(s) in any combination or with other products or materials.

Users of a product or products marked "For Professional Use Only are deemed to declare and acknowledge for themselves professional levels of skill, knowledge, competence and experience in the selection and use of such product(s).

Product Information Sheets are updated from time to time and inquiries should be made on a regular basis to ensure that this is the latest version available.

TETROSYL LIMITED
BEVIS GREEN WORKS
WALMERSLEY
BURY
BL9 6RE
0161 764 5981
0161 797 5899
info@tetrosyl.com