



PRODUCT INFORMATION SHEET

CARLUBE EP 90 GEAR OIL

DESCRIPTION

Carlube EP 90 is a extreme pressure automotive gear oil, manufactured from solvent refined paraffinic base oil and sulfur-phosphorus extreme pressure additives.

ADVANTAGES

- Long service life
- High level of oxidation and corrosion resistance
- Good anti-wear and load carrying capabilities

APPLICATION

Carlube EP 90 is recommended for commercial vehicle, passenger car and construction equipment transmissions, spiral bevel and hypoid drive axles.

PERFORMANCE LEVEL

- API GL4
- MIL-L-2105A
- CS 3000A

PROPERTIES

SAE Viscosity Grade		EP 90
Density @ 15°C		0.890
Kinematic Viscosity (mm ² /s)	@ 40°C	188
	@ 100°C	17.0
Viscosity Index (VI)		96
Pour Point (°C)		-22
Flash Point (°C)		209

AVAILABILITY

500ml – XEW501

1 Litre – XEW011

4.55 Litre – XEW455

25 Litre – YFX025

ENVIRONMENTAL PROTECTION/SAFETY PRECAUTIONS

Do not pour used oil down sewers or drains. Dispose of used oil at your nearest oil-recycling bank. Dispose of empty packs in a responsible manner. Store container in an upright position and secure when transported. Wear goggles if splashing risk. Avoid exposure to oil mist. When using oil do not eat, drink and smoke. Wash hands after use. Always refer to vehicle or engine manufacturers handbook to verify suitability of this product for the vehicle/engine.

**DISCLAIMER**

This Product Information Sheet does not constitute to any extent a fitness for purpose warranty or a quality specification. It is intended to be indicative only of the general characteristics of the product(s) and may not be relied upon (in whole or in part) in substitution of nor as a supplement to any of the information and/or instructions and/or warnings set out on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet (which is available on request).

Neither of the publisher of this Product Information Sheet or the product(s) manufacturer accepts liability for the failure of any person to observe and follow the information and/or instructions and/or warnings on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet.

Any person selecting and using or causing the product(s) to be used for a specific purpose or any third party recommending the product(s) for a specific purpose without in either case first making all appropriate inquiries as to the suitability of the product(s) for the intended purpose does so at his/her/their own risk and no liability is accepted by the publisher or the product(s) manufacturer for any consequent loss, damage or injury, other than such liability as may not (by operation of law) be excluded.

This Product Information Sheet does not apply to the use of the product(s) in any combination or with other products or materials.

Users of a product or products marked "For Professional Use Only are deemed to declare and acknowledge for themselves professional levels of skill, knowledge, competence and experience in the selection and use of such product(s).

Product Information Sheets are updated from time to time and inquiries should be made on a regular basis to ensure that this is the latest version available.

TETROSYL LIMITED
BEVIS GREEN WORKS
WALMERSLEY
BURY
BL9 6RE
0161 764 5981
0161 797 5899
info@tetrosyl.com