



Carlube Triple R 0W-30 Volvo

Carlube Triple R - The Heartbeat of your engine

Technical Data Sheet

High Protection, Performance with Fuel Economy

Carlube Triple R 0W-30 Volvo is a fully synthetic low viscosity engine oil designed for petrol and diesel engines. Providing high levels of wear protection, performance and enhanced fuel economy. Carlube Triple R 0W-30 Volvo has been specially formulated to use in some of the latest Volvo petrol and diesel engines requiring a low viscosity engine oil.

Why Carlube Triple R 0W-30 Volvo is a Protecting, Fuel Efficient Engine Oil


Carlube Triple R 0W-30 Volvo has been developed to meet ACEA A5/B5 and the Volvo 95200377 specification, ensuring exceptional engine performance and protection. It offers excellent engine performance under all driving conditions with enhanced frictional propertiies, providing greater fuel economy.

Carlube Triple R 0W-30 Volvo can provide up to 2.5% fuel economy benefits when compared to a 15W-40 engine oil. This was demonstrated in the CEC M111 fuel economy test and contributes to reducing operating costs for vehicle owners. Although 2.5% may sound like a small amount, this could mean a saving of around 4 pence per litre everytime you fill up, and that's just for changing engine oil!

Another importance factor that needs to be considered when purchasing a lower viscosity engine oil is proof of offering engine and component protection. Carlube Triple R 0W-30 Volvo has been proven to deliver optimum engine protection and delivers 60% more wear protection compared to the ACEA A5/B5 test limits, maximising engine life and performance. Carlube Triple R 0W-30 Volvo provides superior flow properties and therefore rapid oil circulation, which reduces wear due to faster lubrication to key engine parts.







Carlube Triple R 0W-30 Volvo has been formulated using advanced chemistry for higher protection against sludge and deposit build up. Consequently, keeping components clean and allowing the engine to operate as designed.

Customers using Carlube Triple R 0W-30 Volvo will benefit from engine protection and performance with enhanced fuel economy.






Exceptional Range of Passenger Car Performance Specifications

ACEA 2012	A5/B5
API	SL
Volvo	95200377

The chart below shows the performance parameters of the ACEA A5/B5 specification. This demonstrates the wealth of performance Carlube Triple R 0W-30 Volvo offers.



Product Reference

Size	Part No	Barcode
1 Litre	XFW010	
5 Litre	XFW050	
25 Litre	YFW025	
199 Litre	YFW199	



Properties

SAE Viscosity Grade		0W-30
Density @ 15°C		0.8442
Kinematic Viscosity (mm ₂ /s)	@40°C	50.4
	@100°C	9.6
Viscosity Index (VI)		179
Pour Point (°C)		-54
Flash Point (°C)		227
Sulphated Ash (%)		1.16

Environmental Protection & Safety Precautions

Do not pour used surplus oil down sewers or drains. Dispose of used or surplus oil at your nearest oil-recycling bank. Dispose of empty packs in a responsible manner. Store container in an upright position and secure when transported. Wear goggles if splashing risk. Avoid exposure to oil mist. When using oil do not eat, drink or smoke. Wash hands after use.

Disclaimer

This Product Information Sheet does not constitute to any extent a fitness for purpose warranty or a quality specification. It is intended to be indicative only of the general characteristics of the product(s) and may not be relied upon (in whole or in part) in substitution of nor as a supplement to any of the information and/or instructions and/or warnings set out on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet (which is available on request).

Users of a product marked "For Professional Use Only" are deemed to declare and acknowledge for themselves professional levels of skill, knowledge, competence and experience in the selection and use of such product(s).

Product Information Sheets are updated from time to time and inquiries should be made on a regular basis to ensure that this is the latest version available.

