



PRODUCT INFORMATION SHEET

CARLUBE Q III TRANSMISSION FLUID

DESCRIPTION

Carlube Q III Transmission Fluid is a high quality automatic transmission fluid that has been carefully blended from synthetic basestocks and specially balanced additives, to give a product which satisfies the stringent low temperature and frictional requirements of the General Motors Dexron III specification.

ADVANTAGES

- Universal automatic transmission fluid
- Offers smooth and comfortable gear shifting
- Seal and plastic component compatibility
- Anti-corrosion and rust protection
- Low temperature fluidity
- Can be used as ISO VG32 Hydraulic Oil
- Can be used as Power Steering Fluid

APPLICATION

Whilst primarily recommended for passenger cars, coaches, off-highway construction equipment requiring a Dexron III type fluid, the product is also highly recommended against the shown specifications.

PERFORMANCE LEVEL

TRANSMISSIONS

- | | |
|--------------------------|--------------------|
| • DEXRON III | • DEXRON II |
| • WSP-M2C 185-A (Mercon) | • WSP-M2C 138-CJ |
| • WSP-M2C 166-H | • WSP-M2C 195-A |
| • ALLISON C4 | • CATERPILLAR TO-2 |

HYDRAULICS

- | | |
|--------------|----------------|
| • ASTM D2882 | • DENISON HF-O |
| • SUNDSTRAND | • VICKERS |

POWER STEERING

Can be used where any of the above specifications are listed.

PROPERTIES

Appearance		Red Liquid
Density @ 15°C		0.868
Kinematic Viscosity (mm ² /s)	@ 40°C	35.8
	@ 100°C	8.00
Viscosity Index (VI)		200
Pour Point (°C)		-50
Flash Point (°C)		199

AVAILABILITY

500ml – XTE500

1 Litre – XTE100

4.55 Litre – XTE455

25 Litre – YTE025

**ENVIRONMENTAL PROTECTION/SAFETY PRECAUTIONS**

Do not pour used oil down sewers or drains. Dispose of used oil at your nearest oil-recycling bank. Dispose of empty packs in a responsible manner. Store container in an upright position and secure when transported. Wear goggles if splashing risk. Avoid exposure to oil mist. When using oil do not eat, drink and smoke. Wash hands after use. Always refer to vehicle or engine manufacturers handbook to verify suitability of this product for the vehicle/engine.

DISCLAIMER

This Product Information Sheet does not constitute to any extent a fitness for purpose warranty or a quality specification. It is intended to be indicative only of the general characteristics of the product(s) and may not be relied upon (in whole or in part) in substitution of nor as a supplement to any of the information and/or instructions and/or warnings set out on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet (which is available on request).

Neither of the publisher of this Product Information Sheet or the product(s) manufacturer accepts liability for the failure of any person to observe and follow the information and/or instructions and/or warnings on the product(s) and/or on any packaging and/or in the relevant Safety Data Sheet.

Any person selecting and using or causing the product(s) to be used for a specific purpose or any third party recommending the product(s) for a specific purpose without in either case first making all appropriate inquiries as to the suitability of the product(s) for the intended purpose does so at his/her/their own risk and no liability is accepted by the publisher or the product(s) manufacturer for any consequent loss, damage or injury, other than such liability as may not (by operation of law) be excluded.

This Product Information Sheet does not apply to the use of the product(s) in any combination or with other products or materials.

Users of a product or products marked "For Professional Use Only" are deemed to declare and acknowledge for themselves professional levels of skill, knowledge, competence and experience in the selection and use of such product(s).

Product Information Sheets are updated from time to time and inquiries should be made on a regular basis to ensure that this is the latest version available.

TETROSYL LIMITED
BEVIS GREEN WORKS
WALMERSLEY
BURY
BL9 6RE
0161 764 5981
0161 797 5899
info@tetrosyl.com